



**Art.-No.: ED-073602-WW**  
**LED recessed downlight "CANTONE", round, 68x49mm,**  
**7W, 450lm, 2700K, CRI >80, IP20**

LED recessed downlights, Cantone series. Four different covers in white, chrome, chrome matt and brushed metal, available in a round/square version. Operating unit can be dimmed (TRIAC/DALI dimmer), external. Version with CASAMBI® Bluetooth control available.



### TECHNICAL DATA

Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Power Factor	0.85
System power	8.1 W
DC Ready	Yes
Connection cross section	1.5 mm <sup>2</sup>
Dimming	TRIAC, DALI
Electrical version	with external operating device, dimmable
CASAMBI Ready	Yes
Photometrical data	
Light source	LED
Colour temperature	2,700 K
Rated luminous flux	450 lm
Light colour	827
Colour rendering index (CRI)	> 80
Beam angle	38 °
Lifetime (h, at 25°C)	50,000 h, L70
Acceptance tests	
Certifications	CE
Protection class	II
Ingress protection (IP) rating	IP 20
Ambient temperature	-20 to +45 C°
Storage temperature	-25 to +50 C°



Physical data	
Mounting method	recessed ceiling mounted, recessed wall mounted
Housing material	Aluminium
Housing colour	white
Length (L)	92 mm
Width (B)	92 mm
Height (H)	50 mm
Ceiling Cut-out $\varnothing$	68 mm
Recess height	50 mm
Product weight	0.18 kg
Weight incl. Packaging	0.28 kg
Packaging Length (L)	130 mm
Packaging Width (B)	100 mm
Packaging Height (H)	75 mm