



**Art.-No.: YWDZO-LANS-1901-D**  
**LED lamp "ZORRO", wall / ceiling surface mounting,**  
**600x165x63mm, 19W, 2200lm 4000K, CRI >80, IP40,**  
**switchable**



LED ceiling- and wall-mounted luminaire, ZORRO. Housing made from steel plate, white, powder-coated. Diffuser made from plastic (PC), opal, UV-stabilised. Operating unit can be switched or dimmed (DALI dimmer), integrated. Version with CASAMBI® Bluetooth control available. DC compatible. NANO protection on request.

## TECHNICAL DATA

Electrical data	
Input Voltage AC	AC 220-240V / 50-60Hz
Power Factor	0.9
System power	19 W
Inrush current	20 A
Inrush current duration	200 µs
Luminaires on C16A fuse	60 Stk.
Connection cross section	2.5 mm <sup>2</sup>
Electrical version	with internal operating device, switchable
CASAMBI Ready	Yes
Photometrical data	
Light source	LED
Colour temperature	4,000 K
Rated luminous flux	2,200 lm
Luminous efficacy	116 lm/W
Light colour	840
Colour rendering index (CRI)	> 80
Colour tolerance	3
Beam angle	90 °
UGR	26
Lifetime (h, at 25°C)	75,000 h, L80



Acceptance tests	
Certifications	CE
Protection class	I
Ingress protection (IP) rating	IP 40
Ambient temperature	-20 to +25 C°
Physical data	
Mounting method	ceiling mounted
Housing material	Steel sheet
Housing colour	white
Cover material	PC
Length (L)	600 mm
Width (B)	165 mm
Height (H)	63 mm
Product weight	1.4 kg
Weight incl. Packaging	1.7 kg
Packaging Length (L)	704 mm
Packaging Width (B)	166 mm
Packaging Height (H)	57 mm



## LIGHT DISTRIBUTION

